



RECOMMENDED APPLICATIONS XPS FOAM

RECOMMENDED APPLICATIONS ⊕ TECHNICAL DATA

COOLROFOAM	2500 C	2800 C	3035 CS	4000 CS	5000 CS
Load bearing floor slabs *			■	■	■
Domestic floors	■	■	■		
Load bearing floors	■	■	■	■	■
Perimeter* floor slabs			■	■	■
Premier* basement walls			■	■	■
Perimeter* / subsoil water areas			■	■	■
Cavity walls	■		■		
Internal walls		■			
Lost formwork		■			
Cold Bridges		■			
Exterior basement wall insulation		■			
Plaster base		■			
Inverted flat roofs			■	■	■
Duo roofs			■	■	■
Plus roofs			■	■	■
Parking decks				■ 1)	■
Promenade roofs			■	■	■
Roof gardens			■	■	■
Conventional flat roofs	■		■		
Parapet walls	■	■	■		
Pitched roofs	■	■			
Ceilings					
Plasterboard laminates		■			
Sandwich panels	■	■			
Warehouses	■		■	■	■
Roads and railways			■	■	■
Ice rinks			■	■	■

XPS FOAM : Extruded polystyrene foam conforming to DIN EN 13164

Free of CFC, HCFC, and HFC

* = Insulation in direct contact with the ground

1) Not for installation under concrete paving stones

Note : The information submitted in this publication is based on our current knowledge and experience at the time of going to press. It does not imply any legally binding assurance. Attention must be paid to the demands of specific applications, especially the physical and technological aspects of construction and building regulations.